

BECO filter cartridges for food and beverage applications



Powering Business Worldwide

Wide range of filter cartridges offer complete filtration solutions for food and beverage applications

Eaton provides high-quality wrapped and pleated depth filter and membrane filter cartridges.

The BECO® filter cartridge selection offers a wide range of solutions for applications in the food and beverage industry from clarifying and fine filtration with depth filter cartridges (BECO PROTECT®) to the reduction of microorganisms and microbiological stabilisation with membrane filter cartridges (BECO MEMBRAN).

To extend service life and efficiently protect downstream membranes, Eaton can recommend the optimal combination of pre-filter and membrane filter cartridges.

BECO filter cartridges feature a variety of retention ratings, between 0.2 and 150 µm, suitable for an array of liquid filtration applications. In addition to sizes ranging from 10" (25 cm) to 40" (100 cm) and various adapter codes, filter cartridges are available with different filter material. All BECO MEMBRAN filter cartridges are testable for integrity and therefore offer high process reliability for the user.

The product range contains numerous housings and system solutions for the use of depth filter and membrane filter cartridges, such as the BECO INTEGRA® CART stainless steel filter cartridge housings and complex, automatic StepFlow® filtration systems.

Eaton filter cartridges meet national and international quality standards, such as the LFGB standard (German Food, Commodity and Feed Act) in Germany and FDA guidelines (Food and Drug Administration) from the USA. The plastic components meet European Directive (EU) 10/2011.



BECO Filter Cartridges

Selection guide

DEPTH FILTER CARTRIDGES



BECO PROTECT PG

Consist of up to 24 wrapped polypropylene fleeces that are graded from coarse to fine. The funnel design ensures that a wide particle spectrum can be absorbed, with a high retention rating and excellent backwashing capability.



BECO PROTECT CS Cellstream

Innovative wrapped cartridges using adapted BECOPAD® depth filter sheet material. These filter cartridges effectively reduce turbidity, fine colloids and bacteria while offering excellent backflush capabilities.



BECO PROTECT FS FineStream

Specially pleated polypropylene fleeces with a larger filter surface area and good depth effect. The variable flow rate from inside to outside results in minimal product loss during emptying. Self-supporting pleats ensure excellent backflush capabilities.



BECO PROTECT PP Pure

Consist of pleated polypropylene filter material, featuring a high efficiency of retention and a large filter area for high flow rates.

MEMBRANE FILTER CARTRIDGES



BECO MEMBRAN PS Wine

Specifically designed for the final filtration of beer, with a particular focus on long service life and safe retention of microorganisms. Available in retention ratings of 0.45 and 0.65 µm.



BECO MEMBRAN PS Wine

Membrane filter cartridges in 0.45 and 0.65 µm for the final filtration of wine and sparkling wine. They offer long service life and a combination of high microbiological retention with full maintenance.



BECO MEMBRAN PS Aqua

Special polyethersulfone membrane filter cartridges with a retention rate of 0.2 µm offer high flow rates and long service life for the filtration of drinking water.



BECO MEMBRAN PS Pure and PSplus

Pleated membrane filter cartridges constructed from special asymmetrical polyethersulfone (PES) material. With a wide range of retention rates from 0.2 to 1.0 µm, these filter cartridges generally meet all requirements for the final filtration of food and beverages.

FILTER CARTRIDGES FOR SERVICE MEDIA



BECO PROTECT PB

Depth filter cartridges manufactured from thermally bonded, melt-blown polypropylene filter material with high chemical resistance. The mechanical stability of this cartridge is so robust that no inner core or outer cage is required.



BECO PROTECT HF HighFlow

Depth filter cartridges made of pleated, multi-layer and thermally bonded polypropylene filter material, which offers a large surface area, maximum efficiency and exceptionally high flow rates.



BECO PROTECT CL Coreless

Depth filter cartridges made of wrapped polypropylene filter material with different layers from coarse to fine. The filter cartridges are manufactured without a core and with a large diameter to provide high flow rates.



BECO PROTECT KM

Stainless steel filter cartridges that are constructed from porous metal powder (316L) predominately used in steam filtration for the separation of rust particles and abraded matter. These cartridges are designed for liquid filtration at high temperatures.



BECO MEMBRAN H Air and H Air Mini

Membrane filter cartridges that retain contaminants up to 0.01 µm and are primarily used for sterile filtration of gases and air. Available in 1", 5", 10", 20" and 30".

ADAPTER CODES



Code X: Double open end (DOE) without end caps



Code F: Double open end (DOE) with two flat gaskets



Code 0: Single open end (SOE), 2-222 O-ring without spear, external diameter 1.57 in (44 mm) (bottom-most point)



Code 2: Single open end (SOE), 2-222 O-ring, triple bayonet-adapter with spear, external diameter 1.57 in (44 mm) (bottom-most point)



Code 7: Single open end (SOE), 2-226 O-ring, double bayonet-adapter with spear, external diameter 2.2 in (56 mm) (bottom-most point)

Technical data

| | BECO PROTECT PG | BECO PROTECT CS | BECO PROTECT FS | BECO PROTECT PP Pure | BECO PROTECT PB | BECO PROTECT HF | BECO PROTECT CL | BECO PROTECT KM |
|--|---|--|---|---|---|---|---|---|
| Article number | PG002 – PG995 | CS115 | FS002 – FS200 | PPPB6 – PPP10 | PB005 – PB250 | HF010 - HF100 | CL050 - CL400 | KM10 |
| Filter material | Polypropylene (PP) | Special cellulose | Polypropylene (PP) | Polypropylene (PP) | Polypropylene (PP) | Polypropylene (PP) | Polypropylene (PP) | Stainless steel 316L (1.4404) |
| Retention rating (µm) | 0.2, 0.3, 0.5, 0.6, 0.8 1, 2, 3, 5, 10, 15 20, 30, 40, 50, 75 100, 120, 150 | 0.2 | 0.2, 0.3, 0.5, 0.6, 0.8 1, 2, 3, 5, 10, 20 | 0.6, 1.2, 3, 5, 10 | 0.5, 1, 5, 10, 25 | 1, 3, 5, 10 | 5, 10, 20, 40 | 10 |
| Retention efficiency | 99.98% | Nominal | 99.98% | 99.98% | 90% | 99.98% | 99.98% | Nominal |
| Lengths | 9.75", 10", 19.5", 20", 29.5", 30", 40" | 30", 40" | 10", 20", 30", 40" | 10", 20", 30", 40" | 9.75", 10", 19.5", 20", 29.5", 30", 39", 40" | 40" | 40" | 10", 20", 30" |
| Adapter codes | X, F, 0, 2, 7 | 2, 7 | F, 0, 2, 7 | 0, 2, 7 | X, F | U** | X | 7 |
| Cages | Yes | Yes | Yes | Yes | No | Yes | No | No |
| Backwashability | Up to 29 psig (200 kPa, 2 bar) at 176 °F (80 °C) | Up to 29 psig (200 kPa, 2 bar) at 176 °F (80 °C) | Up to 29 psig (200 kPa, 2 bar) at 176 °F (80 °C) | 29.0 psid (200 kPa, 2.0 bar) at 68 °F (20 °C) | Yes | – | – | Up to 14.5 psig (100 kPa, 1 bar) at 77 °F (25 °C) |
| Chemical resistance | pH 1 – 14 | Limited | pH 1 – 14 | pH 1 – 14 | pH 1 – 14 | – | – | pH 1 – 14 |
| Max. operating temperature | 176 °F (80 °C) | 176 °F (80 °C) | 176 °F (80 °C) | 176 °F (80 °C) | 149 °F (65 °C) | 176 °F (80 °C) | 176 °F (80 °C) | 392 °F (200 °C) |
| Max. differential pressure in flow direction | 69 psid (480 kPa, 4.8 bar) at 77 °F (25 °C) 29 psid (200 kPa, 2 bar) at 176 °F (80 °C) | 21.8 psid (150 kPa, 1.5 bar) at 68 °F (20 °C) | 69 psid (480 kPa, 4.8 bar) at 77 °F (25 °C) 29 psid (200 kPa, 2 bar) at 176 °F (80 °C) | 72.5 psid (500 kPa, 5 bar) at 68 °F (20 °C) 29 psid (200 kPa, 2 bar) at 176 °F (80 °C) | 46.4 psid (320 kPa, 3.2 bar) at 68 °F (20 °C) 17.4 psid (120 kPa, 1.2 bar) at 140 °F (60 °C) | 49 psid (340 kPa, 3.4 bar) at 68 °F (20 °C) | 58 psid (400 kPa, 4 bar) at 86 °F (30 °C) 14.5 psid (100 kPa, 1 bar) at 176 °F (80 °C) | – |
| Steam cycles | > 100 at 212 °F (110 °C) in 30 minutes | > 100 at 212 °F (110 °C) in 30 minutes | > 100 at 212 °F (110 °C) in 30 minutes | > 100 at 212 °F (110 °C) in 30 minutes | Not recommended | Max. 10 at 250 °F (121 °C) in 15 minutes | – | – |

| | BECO MEMBRAN PS Beer | BECO MEMBRAN PS Wine | BECO MEMBRAN PS Aqua | BECO MEMBRAN PS Pure | BECO MEMBRAN PSplus | BECO MEMBRAN H Air H Air Mini | |
|--|---|--|--|---|--|--|---|
| Article number | PSB04, PSB06 | PSW04, PSW06 | PSA02 | PSP02, PSP04, PSP06, PSP10 | PES02, PES04, PES06, PES10 | PTC02 | PTM02 |
| Filter material | Polyethersulfone | Polyethersulfone | Polyethersulfone | Polyethersulfone | Polyethersulfone | Teflon (PTFE) | Teflon (PTFE) |
| Retention rating (µm) | 0.45, 0.65 | 0.45, 0.65 | 0.2 | 0.2, 0.45, 0.65, 1.0 | 0.2, 0.45, 0.65, 1.0 | 0.2 | 0.2 |
| LRV (Titer reduction/cm²)* | > 7 | > 7 | > 7 | > 7 1 µm: 6 | > 7 1 µm: 6 | > 7 | > 7 |
| Lengths | 30", 40" | 20", 30" | 20", 30", 40" | 10", 20", 30", 40" | 10", 20", 30", 40" | 10", 20", 30" | 1", 5" |
| Adapter codes | 2, 7 | 2, 7 | 2, 7 | 0, 2, 7 | 0, 2, 7 | 7 | 1, 4, 7 |
| Cages | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Pressure hold test Test pressure in bar and diffusion rate per 10" | PSB04 17.4 psig (1.2 bar) ≤ 15 ml/min PSB06 11.6 psig (0.8 bar) ≤ 5 ml/min | PSW04 21.8 psig (1.5 bar) ≤ 15 ml/min PSW06 14.5 psig (1 bar) ≤ 10 ml/min | PSA02 36 psig (2.5 bar) ≤ 20 ml/min | PSP02 36 psig (2.5 bar) ≤ 20 ml/min PSP04 21.8 psig (1.5 bar) ≤ 15 ml/min PSP06 14.5 psig (1 bar) PSP10 10.2 psig (0.7 bar) ≤ 15 ml/min | PES02 35 psig (2.4 bar) ≤ 20 ml/min PES04 24.6 psig (1.7 bar) ≤ 20 ml/min PES06 14.5 psig (1 bar) PES10 8.7 psig (0.6 bar) ≤ 20 ml/min | PTC02 Nitrogen diffusion at 68 °F (20 °C) per 10" ≤ 7 ml/min at 10.2 psig (70 kPa, 700 mbar) with 60% isopropanol | PTM02 Bubble point test at 73 °F (23 °C) ≥ 10.2 psig (1000 mbar) with 60% isopropanol |
| Backwashability | Limited 29 psid (200 kPa, 2 bar) at 68 °F (20 °C) | Limited 29 psid (200 kPa, 2 bar) at 68 °F (20 °C) | 29 psid (200 kPa, 2 bar) at 68 °F (20 °C) | Limited 29 psid (200 kPa, 2 bar) at 68 °F (20 °C) | – | – | – |
| Chemical resistance | pH 1 – 14 | pH 1 – 14 | pH 1 – 14 | pH 1 – 14 | pH 1 – 14 | pH 1 – 14 | pH 1 – 14 |
| Max. operating temperature | 176 °F (80 °C) | 176 °F (80 °C) | 176 °F (80 °C) | 176 °F (80 °C) | 176 °F (80 °C) | 176 °F (80 °C) | 176 °F (80 °C) |
| Max. differential pressure in flow direction | 72.5 psid (500 kPa, 5 bar) at 68 °F (20 °C) 4 psid (30 kPa, 0.3 bar) at 250 °F (121 °C) | 72.5 psid (500 kPa, 5 bar) at 68 °F (20 °C) 4 psid (30 kPa, 0.3 bar) at 250 °F (121 °C) | 72.5 psid (500 kPa, 5 bar) at 68 °F (20 °C) 4 psid (30 kPa, 0.3 bar) at 250 °F (121 °C) | 72.5 psid (500 kPa, 5 bar) at 68 °F (20 °C) 4 psid (30 kPa, 0.3 bar) at 250 °F (121 °C) | 72.5 psid (500 kPa, 5 bar) at 77 °F (25 °C) 4 psid (30 kPa, 0.3 bar) at 250 °F (121 °C) | 72.5 psid (500 kPa, 5 bar) at 68 °F (20 °C) 7.25 psid (50 kPa, 0.5 bar) at 273 °F (134 °C) | 72.5 psid (500 kPa, 5 bar) at 68 °F (20 °C) 7.25 psid (50 kPa, 0.5 bar) at 273 °F (134 °C) |
| Steam cycles | ≥ 100 at 221 °F (105 °C) in 30 minutes | ≥ 100 at 221 °F (105 °C) in 30 minutes | ≥ 100 at 221 °F (105 °C) in 30 minutes | ≥ 100 at 221 °F (105 °C) in 30 minutes | ≥ 100 at 230 °F (110 °C) in 30 minutes | ≥ 150 at 273 °F (134 °C) in 20 minutes | 50 273 °F (134 °C) in 20 minutes |

* Please see technical data sheets for further information about the used test organisms ** Code U (SOE) for large diameter filter cartridge only



Application examples

| Filtration level | Wine | Beer | Fruit juice | Water | Spirits |
|---|---|---|---|---|---|
| Rinsing water filtration (two-level combination possible) | BECO PROTECT PG; FS (0.5 – 10 µm) | BECO PROTECT PG; FS (0.5 – 10 µm) | BECO PROTECT PG; FS (0.5 – 10 µm) | BECO PROTECT PG; FS (0.5 – 10 µm) | BECO PROTECT PG; FS (0.5 – 10 µm) |
| Particle filtration | BECO PROTECT PG; FS; PP Pure (2 – 5 µm) | BECO PROTECT PG; FS; (5 – 20 µm) | BECO PROTECT PG; FS; (5 – 10 µm) | BECO PROTECT PG; FS; (5 – 10 µm) | BECO PROTECT PG; FS; (5 – 20 µm) |
| Fine filtration | BECO PROTECT PG; FS; PP Pure (0.5 – 1 µm) | BECO PROTECT PG; FS; (0.5 – 2 µm) | BECO PROTECT PG; FS; PP Pure (0.5 – 1 µm) | BECO PROTECT PG; FS; PP Pure (1 – 3 µm) | BECO PROTECT PG; FS; PP Pure (0.5 – 1 µm) |
| Membrane protection | BECO PROTECT PG; CS; FS; PP Pure (0.2 – 0.6 µm) | BECO PROTECT PG; FS; (0.3 – 0.6 µm) | BECO PROTECT PG; CS; FS; PP Pure (0.2 – 0.6 µm) | BECO PROTECT PG; FS; PP Pure (0.3 – 1 µm) | – |
| Membrane filtration | BECO MEMBRAN PS Wine, PSplus (0.45 – 0.65 µm) | BECO MEMBRAN PS Beer, PSplus (0.45 – 0.65 µm) | BECO MEMBRAN PS Pure, PSplus (0.2 – 0.45 µm) | BECO MEMBRAN PS Aqua, PSplus (0.2 µm) | – |
| Process water filtration | BECO PROTECT HF; CL (1 – 40 µm) | BECO PROTECT HF; CL (1 – 40 µm) | BECO PROTECT HF; CL (1 – 40 µm) | BECO PROTECT HF; CL (1 – 40 µm) | BECO PROTECT HF; CL (1 – 40 µm) |
| Rinse water filtration | BECO PROTECT PB (1 – 10 µm) | BECO PROTECT PB (1 – 10 µm) | BECO PROTECT PB (1 – 10 µm) | BECO PROTECT PB (1 – 10 µm) | BECO PROTECT PB (1 – 10 µm) |
| Steam filtration | BECO PROTECT KM (10 µm) | BECO PROTECT KM (10 µm) | BECO PROTECT KM (10 µm) | BECO PROTECT KM (10 µm) | BECO PROTECT KM (10 µm) |
| Gas filtration | BECO MEMBRAN H Air; H Air Mini (0.2 µm) | BECO MEMBRAN H Air; H Air Mini (0.2 µm) | BECO MEMBRAN H Air; H Air Mini (0.2 µm) | BECO MEMBRAN H Air; H Air Mini (0.2 µm) | BECO MEMBRAN H Air; H Air Mini (0.2 µm) |

FILTER CARTRIDGE HOUSINGS



BECO INTEGRA CART KA

These filter cartridge housings are manufactured from AISI 316L stainless steel and can be used for the liquid filtration in the food and beverage industry. They are available in 1-, 3-, 5-, 8-, 12-, 18-, 24- and 30-fold cartridge versions for pre-filtration or sterile filtration purposes.



BECO INTEGRA CART KHF/KCL

Manufactured of stainless steel AISI 316L and can be applied for the filtration of liquids with high flow rates in Life Science applications. This series is available as a 1 x 40" version.



BECO INTEGRA CART KK

These filter cartridge housings are manufactured from AISI 316L stainless steel and designed for pressurized air or steam filtration applications.



BECO INTEGRA CART KLAV


These filter cartridge housings are manufactured from AISI 316L stainless steel and are used as vent filter housings for gas filtration. This series is suitable for sterile filtration for filter cartridges with a code 1 adapter.

TESTING DEVICES



BECO LiquiControl₂

The BECO LiquiControl₂ index measuring device is used to determine the filterability of any ready-to-bottle beverage. Prior to membrane filtration, a sample is filtered under defined conditions (constant pressure) through a reference membrane.



BECO Control Mini

The BECO Control Mini integrity test unit facilitates the execution of integrity tests for membrane filter cartridges. The extremely precise measurement of the pressure drop in mbar guarantees that the integrity of the membrane filter cartridges is maintained and thus ensures guaranteed microbiological stability.



BECO MAX₂

The fully automatic integrity test unit BECO MAX₂ is designed for the regular testing of membrane filter cartridges, and features an easy-to-use keypad and backlit four-line display in a stainless steel housing.



Powering Business Worldwide

North America

44 Apple Street
Tinton Falls, NJ 07724
Toll Free: 800 656-3344
(North America only)
Tel: +1 732 212-4700

Europe/Africa/Middle East

Auf der Heide 2
53947 Nettersheim, Germany
Tel: +49 2486 809-0

Friedensstraße 41
68804 Altlufßheim, Germany
Tel: +49 6205 2094-0

An den Nahewiesen 24
55450 Langenlonsheim, Germany
Tel: +49 6704 204-0

Greater China

No. 7, Lane 280,
Linhong Road
Changning District, 200335
Shanghai, P.R. China
Tel: +86 21 5200-0099

Asia-Pacific

100G Pasir Panjang Road
#07-08 Interlocal Centre
Singapore 118523
Tel: +65 6825-1668

**For more information, please
email us at filtration@eaton.com
or visit www.eaton.com/filtration**

© 2022 Eaton. All rights reserved. All trademarks and registered trademarks are the property of their respective owners. All information and recommendations appearing in this brochure concerning the use of products described herein are based on tests believed to be reliable. However, it is the user's responsibility to determine the suitability for his own use of such products. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Eaton as to the effects of such use or the results to be obtained. Eaton assumes no liability arising out of the use by others of such products. Nor is the information herein to be construed as absolutely complete, since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations.

US
1 A 4.5
06-2022

