# VIKING PUMP<sup>®</sup>



#### **STERILOBE<sup>®</sup> SERIES**

ROTARY LOBE PRODUCT LINE





#### **FEATURES & BENEFITS**

#### **CLEANABILITY**

- Cover joint profile improves hygienic characteristics & self-draining capabilities
- Clean & corrosion resistant stainless gear cover & powder coated bearing housing

#### **EASE OF MAINTENANCE**

- Front loading seals can be changed while the pump is still in-line
- Seal positioned for optimal lubrication, maximizing seal life
- Hassle free gearbox maintenance with sealed for life bearings

#### PERFORMANCE

- Standard bi-wing rotors offer application flexibility & good solids handling capabilities
- Multi-lobe rotors reduce shear & pulsation effect; ideal for sensitive media
- Innovative cusps with reliefs allow for easier cleaning and self draining with improved efficiency

PERFORMANC	E
------------	---

MODELS										
	Displacement		Max Pressure		Max Speed	Standard Ports		Max Capacity		
Model	USG/rev.	l/rev.	PSI	BAR	RPM	In	mm	GPM	m³/h	
SLAS	0.0103	0.039	218	15	1400	.75	19	14	3.18	
SLAL	0.0156	0.059	145	10	1400	1	25	22	5	
SLBS	0.0214	0.081	218	15	1200	1	25	25.7	5.8	
SLBL	0.0322	0.122	145	10	1200	1.5	38	38.7	8.8	
SLCS	0.0446	0.169	218	15	1200	1.5	38	53.6	12.2	
SLCL	0.0671	0.254	145	10	1200	2	50	80.5	18.3	
SLDS	0.093	0.352	218	15	1000	1.5	38	93	20.5	
SLDL	0.1395	0.528	145	10	1000	2	50	139.5	31.7	
SLES	0.1934	0.732	218	15	800	2	50	154.7	35.1	
SLEL	0.2903	1.099	145	10	800	3	76	232.3	52.8	
SLFS	0.4026	1.542	218	15	600	3	76	241.5	54.8	
SLFL	0.6036	2.285	145	10	600	4	101	362.2	82.3	
SLGS	0.8374	3.17	218	15	600	4	101	502.5	114.1	
SLGL	1.2559	4.754	145	10	600	6	152	753.5	171.1	





VISCOSITY to 910,000 SSU (200,000 cSt)



**TEMPERATURE** to +300°F (+150°C) \_\_\_\_\_

#### PORTING

- Complete range of hygienic clamp, screw, flange & industrial screw connections
- Tri-clamp, flanged, DIN, IMDA, NPT, BSP, etc.

#### SEALING

- Single mechanical
- Single mechanical with flush or quench
  - Standard Seal Faces: C/SiC
  - Standard O-rings & Cover Seals: EPDM/FDA
  - Optional Faces: SiC/SiC
  - Optional O-rings & Cover Seals: FKM, Buna, Silicone, FFKM
- Double mechanical with flush
  - Seal Faces: C/SiC/SiC/C or SiC/SiC/SiC/C
  - Standard O-rings & Cover Seals: EPDM/FDA
  - Optional Faces: SiC/SiC
  - Optional O-rings & Cover Seals: FKM, Buna, Silicone, FFKM

# **ROTOR & CASING OPTIONS**

- 316L stainless steel pump casing with interior finished to Ra of 24μin (0.6μm).
- 316L stainless steel rotors
- 1.4435 low ferrite stainless steel optional
- Improved surface finishes & electropolishing optional
- Bi-wing rotors standard
  - No timing required
  - Preferred for large solids such as fruit pieces, nut kernels, cheese curds or meats
- Multilobe rotors optional
  - · Provides reduced shear on shear sensitive fluids
  - Improved performance on thin liquids resulting in less pulsation at higher pressures

### OPTIONAL COMPLIANCE CERTIFICATION DOCUMENTATION & PERFORMANCE TESTS

- Pump Performance
- General Compliance
- Media Contact
- Media Contact Elastomers
  Seal Face
- Surface FinishPump Assembly Inspection

# **TYPICAL APPLICATIONS**

Pharmaceutical

Foods

- al Beverage
- Personal Care
- Dairy
- Confectionary

#### **BENEFITS OF MAINTENANCE KITS**

- Everything you need in one place
- Reduce frequency of repairs
- Increase service life
- Increase uptime
- Save time & money
- Kits include exploded diagram & parts list

#### **REBUILD VS. REPLACE**

- Kits are designed to save time & money, making preventive maintenance easier & more cost-effective
- Pumps are designed & built to the highest standards, for long life & to be rebuilt instead of replaced when applicable
- Tool kits also available

**CONTACT YOUR STOCKING DISTRIBUTOR TODAY** 

# **VIKING PUMP**°

VIKING PUMP, INC. A Unit of IDEX Corporation 406 State Street Cedar Falls, Iowa 50613 U.S.A. vikingpump.com



list

Certified

Documents

ATEX & CE

Chemical

Metallic Insp Components