


**Wilden®**  
PS8 51 mm (2") Pro-Flo® SHIFT

**VS** **ARO®**  
2" ARO® EXP Series



In controlled laboratory testing witnessed by a panel of engineers, pump experts, and industry professionals, competitive pumps were tested and judged against the revolutionary patent pending Pro-Flo® SHIFT. The witnesses were asked to select a common operating parameter they see in the field (2.1 bar (30 psig) fluid head pressure and a flow requirement of 320 lpm (85 gpm)). We ran each pump at the inlet air pressure required to meet the flow requirement set by the witnesses and recorded the air consumption. We think you'll find the results compelling.



#### PERFORMANCE

**69%**  
**INCREASE**  
**IN PRODUCTIVITY**  
**VS. THE COMPETITION**  
USING THE SAME COMPRESSOR



#### Efficiency Comparison

	Wilden® PS8 Pro-Flo® SHIFT	2" ARO® EXP Series
Flow rate*	320 lpm (85 gpm)	320 lpm (85 gpm)
Air in SCFM	42.6	71.8
Strokes per minute (maintenance indicator)	120	144
Fluid pumped per SCFM (used to judge efficiency)	7.57 lpm (2.00 gpm)	4.47 lpm (1.18 gpm)
Reduced air consumption over competition by	41%	
Air consumption increase over Pro-Flo® SHIFT		69%
Annual savings to run 10 pumps	\$48,057.18	
Increase in productivity by using Pro-Flo® SHIFT versus the Competition	69%	

\* selected by a group of experts as a common parameter in the field

Make the SHIFT to Pro-Flo® SHIFT  
and **Experience**

- Higher productivity with reduced energy
- Easily reduce your carbon footprint
- Additional product yield offers great capacity and scalability
- Proven Pro-Flo technology
- ATEX compliant
- No additional setup or hard to read curves



**WILDEN®**  
Part of Pump Solutions Group  
A DOWDER COMPANY

wildenpump.com

See the proof at  
<http://www.profloshift.com/video/head-to-head/aro-exp>



ARO® is a registered trademark of Ingersoll Rand